

EXPANDED METAL

MAGNUS REF #:	SIZE OF MESH SWM X LWM	STRAND		WEIGHT / 2.4 X 1.2
		WIDTH	THICKNESS	
36R-A	3 X 6	1.0	0.6	7.54
510R-A	5 X 10	1.0	1.0	8.22
820R-A	8 X 20	2.0	1.0	10.17
1630R-A	16 X 30	2.5	1.6	11.30
1840R-A	18 X 40	2.5	1.6	10.05
1540R-C	18 X 40	2.6	2.4	15.70
3055R-D	30 X 55	2.6	2.9	11.40
3060R-D	30 X 60	2.7	2.9	11.80
3060R-E	30 X 60	4.5	4.4	29.80
3060R-E	30 X 60	4.5	4.4	29.80
3680R-D	36 X 80	2.6	2.9	9.50
5080R-D	50 X 80	2.6	2.9	6.80
48115R-E	48 X 115	4.0	4.4	16.60
48115R-EE	48 X 115	5.0	4.4	20.70

THE ABOVE MESH HAS A RAISED SURFACE

510F-A	5 X 10	1.2	1.0	8.22
820F-A	8 X 20	2.0	1.0	10.17
1630F-A	16 X 30	2.6	1.6	11.80
1235F-A	12 X 35	3.0	1.6	15.26
1840F-A	18 X 40	2.6	1.6	10.40
1840F-C	18 X 40	2.6	2.4	15.70
3055F-A	30 X 55	2.6	1.6	6.30
3055F-B	30 X 55	2.6	1.9	7.40
3055F-C	30 X 55	3.8	2.4	13.70
3055F-D	30 X 55	2.6	2.9	11.40
3055F-DD	30 X 55	3.8	2.9	16.60
3055F-PIG	30 X 55	8.7	2.9	38.00
3080F-C	30 X 80	4.5	2.5	14.96
5080F-C	50 X 80	4.0	2.4	8.70

THE ABOVE MESH HAS A FLATTENED SURFACE

4014W-A	40 X 140	6.0	4.5	27.47
3512W-A	35 X 120	6.0	4.5	33.91
3512W-B	35 X 120	8.0	4.5	44.08
3512W-C	35 X 120	10.0	4.5	50.87
3512W-D	35 X 120	10.0	6.0	67.82

THE ABOVE MESH IS USED PRIMARILY FOR WALKWAYS